




NX 48H Bond PVC 75 Ohm Coaxial Cable Drop Cable



Rev. 14 June 2005



Cu PEE Xgas A/P/A/Cop CuSn Pvc

Construction and Dimensions

	materials	dimensions mm	tolerance mm
A. Inner conductor : Solid soft annealed copper	Cu	1,13	±0,016
B. Dielectric : Foam polyethylene Xgas injected	PEE Xgas	4,80	±0,05
C. Outer conductor Foil : Aluminum/Polyester/Aluminum/Copolymer Bonded to the dielectric	A-P-A-Cop	100%	
D. Braid : Tinned copper wire Coverage : Visual coverage	CuSn	70%	
E. Sheath Not contaminating PVC lead free UV resistant	Pvc	6,80	±0,10

Electrical Characteristics

Impedance :		75±1	Ω
Capacitance :		52±1	pF/m
Velocity ratio :		85	%
Voltage test of sheath :		2	kVdc
Resistance at 20° C	Inner conductor	17	Ω/km
	Outer conductor	13	Ω/km

Attenuation at 20° C

MHz	dB/100m	MHz	dB/100m	MHz	dB/100m	MHz	dB/100m
50	4,1	862	16,8	1750	24,4	3000	32,7
200	7,8	1000	18,1	2150	27,3		
450	11,9	1350	21,2	2400	29,0		

Return Loss SRL

5-470	MHz	> 35 dB
470-1000	MHz	> 33 dB
1000-3000	MHz	> 30 dB

Transfer Impedance

5-30	MHz	< 5 mOhm/m
------	-----	------------

Screening Efficiency

30-1000	MHz	> 90 dB
1000-2000	MHz	> 85 dB
2000-3000	MHz	> 75 dB

Mechanical Characteristics

Minimum static bending radius :	35/70	mm
Total weight :	48,90	g/m
Operating temperature :	-40°C to +70°C	

BETA CAVI srl - Viale delle Industrie 84091 Battipaglia (SA) - Italy - <http://www.betacavi.it> email : info@betacavi.it

BETACAVI

PRO SAF d.o.o., Pod Hruševco 30, 1360 Vrhnika, SLOVENIJA
PRO SAF proizvodnja, trgovina, storitve in inženiring d.o.o.

tel.: +386 1 750 28 28 • fax: +386 1 750 28 29
<http://www.pro-saf.si> • e-mail: pro.saf@siol.net

